



Earth Leakage Circuit Breaker

Part No.

DZ47LE+MX



Feature

- Leakage, short-circuit and overload protection
- Optional over-voltage, under-voltage or shunt protection.
- Used for circuit of AC 50/60Hz, 230V/400V, 100A

ORDERING INFORMATION

DZ 47LE + MX - 63 - 1 N - 32

① ② ③ ④ ⑤ ⑥

- ① Series: DZ47LE series
- ② I DC24A; II ac220v; III AC380V
- ③ Shell grade: 32, 63, 100
- ④ Pole: 1, 2, 3, 4
- ⑤ Neutral: N
- ⑥ Rated current: 32, 63, 100A

TECHNICAL DATA

Shell grade Inm (A)	Poles P	Neutral	Rated current In (A)	Short-circuit breaking capacity			Rated residual action current IΔn (mA)	Rated residual non-action current IΔno (mA)	Release type
				V	Icn	cosΦ			
32	1	N	6, 10, 16, 20, 25, 32	230	4000	0.7	30	15	C
	2						50	25	
	3			75			40		
	3	N		100			50		
	4			300			150		
63	1	N	40, 50, 63	230	4000	0.8	30	15	D
	2						50	25	
	3			75			40		
	3	N		100			50		
	4			300			150		
100	1	N	63, 80, 100	230	10000	0.8	30	15	C, D
	2						50	25	
	3			75			40		
	3	N		100			50		
	4			300			150		

DIMENSION (mm)

