



## TECHNICAL DATA

Model	Rated current AC-380V	Motor P (KW)					
		220V	380V	415V	440V	660V	
CJX2-09	9	2.2	4	4	4	5.5	3P+NO /3P+NC
CJX2-12	12	3	5.5	5.5	5.5	7.5	
CJX2-18	18	4	7.5	9	9	9	
CJX2-25	25	5.5	11	11	11	15	
CJX2-32	32	7.5	15	15	15	18.5	
CJX2-40	40	11	18.5	22	22	30	
CJX2-50	50	15	22	25	30	33	3P+NO+NC
CJX2-65	65	18.5	30	37	37	37	
CJX2-80	80	22	37	45	45	45	
CJX2-95	95	25	45	45	45	45	

Model		CJX2-09	CJX2-12	CJX2-18	CJX2-25	CJX2-32	CJX2-40	CJX2-50	CJX2-65	CJX2-80	CJX2-95
Rated current I <sub>e</sub> A (AC-3)	380V	9	12	18	25	32	40	50	65	80	95
	660V	6.6	8.9	12	18	21	34	39	42	49	49
Rated current I <sub>e</sub> A (AC-4)	380V	3.5	5	7.7	8.5	12	18.5	24	28	37	44
	660V	1.5	2	3.8	4.4	7.5	9	12	14	17.3	21.3
Conventional thermal current		25	25	32	40	50	60	80	80	125	125
Rated operational voltage		380V 660V									
Rated insulation voltage		690V									
Electric durability AC-3 x10 <sup>4</sup> AC-4 x10 <sup>4</sup>		100	100	100	100	80	80	60	60	60	60
		20	20	20	20	20	15	15	15	10	10
Mechanical durability x10 <sup>4</sup>		1000				800				600	
Operating rate AC-3 cycles/h		1200	1200	1200	1200	600	600	600	600	600	600
Operating rate AC-4 cycles/h		300			150						

### Coil

Coil voltage (Us) V	24 48 110 220 380										
Pull-in voltage V	0.85~1.10 Us										
Release voltage V	0.2~0.75 Us										
Inrush VA	76	76	76	110	110	230	230	230	230	230	230
Sealed VA	9.4	9.4	9.4	9.4	11	11	26	26	26	26	26

### Accessories

Conventional thermal current		10A										
Minimum load		6V 10mA										
Terminal connector	Wire quantity	1 2	1 2	1 2	1 2	1 2	1 2	1 2	1 2	1 2	1 2	1 2
	Soft wire	2.5 2.5	2.5 2.5	4 4	4 4	6 6	10 10	16 16	16 16	50 25	50 25	
	Hard wire	4 4	4 4	6 6	6 -	10 10	10 10	25 -	25 -	50 -	50 -	