



Industrial & Electrical Components

General Purpose Power Relay

Part No.

HHC68AZ



- General purpose power relay
- For plug-in socket, 35mm DIN rail
- Mechanical indicator + lockable test button
- LED option

CONTACT

Arrangement	2A, 2B, 2C
Contact Material	Silver Alloy
Contact Resistive	Max.: 100 mΩ
Rating	
Resistive load (cosφ=1)	10A 240VAC/28VDC
Max. Switching Voltage	277VAC/28VDC
Min. Breaking Capacity	0.3W
Expected life	
Mechanical	1×10 ⁷
Electrical	1×10 ⁵

CHARACTERISTICS

Operate Time	20msec. Max.
Release Time	20msec. Max.
Initial breakdown voltage	
Between Coil & Contact	1500VAC (50/60Hz) for 1 min.
Between Open Contacts	1000VAC (50/60Hz) for 1 min.
Insulation Resistance	Min.100MΩ (500 VDC)
Shock: Endurance	10G
Damage	100G
Vibration Endurance	10 to 55Hz, 1.0mm D.A.
Damage	10 to 55Hz, 1.0mm D.A.
Ambient temperature	-55°C ~ +70°C
Unit weight	35g

ORDERING INFORMATION

e.g

HHC68AZ - 2C - 12D - L

①

②

③

④

① Part No.

② Contact arrangement:

2C=2C/O;

③ Coil Voltage: 12D=12VDC

④ L = LED indication

COIL DATA (at 20°C)

Rated Voltage	Pick-up Voltage VDC (Max)	Drop-out Voltage VDC (Min)	Coil Resistance (Ω) ± 10%	Nominal operating Power	Max.Allowable Voltage (VDC)
12VDC	9.00	1.20	160.00	0.9W	110% of nominal voltage
24VDC	18.00	2.40	640.00		
48VDC	36.00	4.80	2560.00		
110VDC	82.50	11.00	13450.00		
12VAC	9.60	3.60	42.00	1.2VA	
24VAC	19.20	7.20	168.00		
48VAC	38.40	14.40	672.00		
220VAC	176.00	66.00	14100.00		

DIMENSIONS

Unit: mm

