



Industrial & Electrical Components

Relay Socket


Part No.

TP58X
TP511X
TP514X

TP58X




OUTLINE DIMENSIONS




SPECIFICATION

Rated Load	Current	7A
	Voltage	300V
Dielectric Strength		2500V
Ambient Temperature		-40~+75°C
Socket Material		Flame retardance PA66+GF(V1/V0)
Contacts Spring Material		QSn6.5-0.1
Clamp Spring Material		Plastic
Module		No

MOUNTING DIMENSIONS




DIAGRAM



TP511X




OUTLINE DIMENSIONS




SPECIFICATION

Rated Load	Current	7A
	Voltage	300V
Dielectric Strength		2500V
Ambient Temperature		-40~+75°C
Socket Material		Flame retardance PA66+GF(V1/V0)
Contacts Spring Material		QSn6.5-0.1
Clamp Spring Material		Plastic
Module		No

MOUNTING DIMENSIONS




DIAGRAM



TP514X




OUTLINE DIMENSIONS



SPECIFICATION

Rated Load	Current	7A
	Voltage	300V
Dielectric Strength		2500V
Ambient Temperature		-40~+75°C
Socket Material		Flame retardance PA66+GF(V1/V0)
Contacts Spring Material		QSn6.5-0.1
Clamp Spring Material		Plastic
Module		No

MOUNTING DIMENSIONS



DIAGRAM

